

IP-1015BX



IP-1015BX is a device that receives a digital audio signal, converts it with an analog audio signal, and sends it to a line or 8OHM Level. You can easily broadcast the sound source received from the IP speaker/IPA system. Small size is efficient to reduce the installation space and reduce costs.

- Inter-M AOE-based network audio transmitter
- Can be used with Inter-M IP speaker/IPA system
- 1CH line output, 1CH 8ohm speaker output
- WAV, MP3 file streaming available
- It is possible to integrate with external devices through contact input and output.
- 1GB of internal memory for storing music sources (Up to 32GB of expansion through MicroSD card)
- Device control through the Web GUI
- Support for installation of table types or walls

	IP-1015BX	
Amplifier		
Rated output power (8Ω,1kHz sine wave)	3.7W (PoE 802.3af)	10W (PoE+ 802.3at)
Frequency response (1W @ 8Ω, ±3dB)	20Hz - 20kHz	
THD+N (20Hz HPF, AES17 LPF, 8Ω)	Less than 3%	
Line output		
Maximum audio output	+6dBV ± 3dB	
Frequency response	20Hz - 20kHz (+1/-3dB)	
THD+N (20Hz HPF, AES17 LPF)	Less than 0.1%	
S/N (20Hz HPF, AES17 LPF, A-WTD)	Better than 91dB	
Contact I/O		
Contact Input(1CH)	Dry contact	
Contact Output(1CH)	Dry contact(N.O : Normally Open)	
Storage		
MicroSD	Max 32GB	
Network		
Ethernet	10/100 BASE-TX PoE	
Power	PoE (IEEE 802.3af, IEEE 802.3at)	
Operating Temperature	-20 ~ +50	
Power Consumption	PoE(IEEE 802.3af) : 44~57 VDC, Max 12.95W PoE+(IEEE 802.3af) : 50~57 VDC, Max 25.5W	
Weight(Set)	0.24kg/0.53lb	
Dimensions(Set)	123(W) x 80(H) x 30.6(D)mm 4.84(W) x 3.14(H) x 1.2(D)in	

